(REV. 1-98) TRANSMITTAL LETTER TO THE UNITED STATES 365-428PCT DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371 INTERNATIONAL APPLICATION NO. INTERNATIONAL FILING DATE PRIORITY DATE CLAIMED • PCT/FI98/00329 / April 1998-11 April 1997 ✓ TUTLE OF INVENTION POLYOL AND COMPLEX ESTERS FOR USE WITH, IN PARTICULAR, FLUORINATED REFRIGERANTS APPLICANT(S) FOR DO/EO/US KOISTINEN, Jari; RISSANEN, Kari; SILVENNOINEN, Laura; KOSKIMIES, Salme / Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information: 1. This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371. This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371. This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39 (1). A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date A copy of the International Application as filed (35 U.S.C. 371(c)(2)) a. X is transmitted herewith (required only if not transmitted by the International Bureau). (appln. encl. W098/46706) has been transmitted by the International Bureau. is not required, as the application was filed in the United States Receiving Office (RO/US). A translation of the International Application into English (35 U.S.C. 371(c)(3)). Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(2)). are transmitted herewith (required only if not transmitted by the International Bureau). O'NE STATE have been transmitted by the International Bureau. have not been made; however, the time limit for making such amendments has NOT expired. d. Mave not been made and will not be made. 8, A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)). 9. An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)). A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 10. (35 U.S.C. 371(c)(5)). Items 11. to 16. below concern document(s) or information included: An Information Disclosure Statement under 37 CFR 1.97 and 1.98. International Search Report An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included. 13. A FIRST preliminary amendment. A SECOND or SUBSEQUENT preliminary amendment. A substitute specification. A change of power of attorney and/or address letter. Other items or information: PCT Request (PCT/RO/101) International Search Report (PCT/IPEA/409) w/Amended Claims) Zero (0) Sheet of Formal Drawing

	•		*	514 Rec	汕	PCTPTO) 8 OCT 1	999
U.S. API	PLICATION NO (if known, see 37	402674	IONAL APPLICATION NO PCT/FI98/00329	2		365	-428PCT	
BAS Neit nor i	her international _l nternational searc	s are submitted: FEE (37 CFR 1.492(a)(1)-(5) preliminary examination fee (3 ch fee (37 CFR 1.445(a)(2)) pa arch Report not prepared by the	7 CFR 1.482) id to USPTO	\$970.00	CA	LCULATIONS	PTO USE OF	NLY
		nary examination fee (37 CFR lonal Search Report prepared by		\$840.00				
		hary examination fee (37 CFR 1 ch fee (37 CFR 1.445(a)(2)) pa		\$760.00				
Interbut a	national prelimin all claims did not	nary examination fee (37 CFR asatisfy provisions of PCT Artic	1.482) paid to USPTO cle 33(1)-(4)	\$670.00				
and	all claims satisfie ENTER AP	nary examination fee (37 CFR) and provisions of PCT Article 33 PPROPRIATE BASIC	FEE AMOUNT =	. \$96.00	\$	970.00		
		for furnishing the oath or deck est claimed priority date (37 Cl	FR 1.492(e)).	30	\$			-
	CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE				
Tota	Claims	23 - 20 =	3	X \$18.00	\$	54.00		
Inde	pendent Claims	3 - 3 =	_ =====	X \$78.00	\$			
		DENT CLAIM(S) (if applicable	e) Yes	+ \$260.00	\$	260.00		
## 1			OF ABOVE CALCULA	TIONS =	\$	1284.00		
		ling by small entity, if applicable and the small entity, if applicable and the small entity, if applicable and the small entity is applicable.			\$			
ļinus	also be filed (1ve	ote 37 CTR 1.5, 1.27, 1.20).	SUB'	TOTAL =	\$	1284.00		
Proc	essing fee of \$13	0.00 for furnishing the English est claimed priority date (37 C	translation later than]20	\$	1401.00		
mon	ths from the earn	est claimed priority date (37 C	TOTAL NATION	AL FEE =	\$	1284.00		
Fee	for recording the	enclosed assignment (37 CFR ppropriate cover sheet (37 CFR	1.21(h)). The assignment r	nust be	\$	40.00		
acco	mpanied by an ap	ppropriate cover sheet (37 Cr K	TOTAL FEES ENC	LOSED =	\$	1324.00		
10			TOTALLES			Amount to be: refunded	\$	
2.5						charged	S	
a. [>	Please charge A duplicate co	amount of \$ <u>1324.00</u> to comy Deposit Account. Noopy of this sheet is enclosed.	in the amount of	\$ to				
с. [overpayment t	oner is hereby authorized to che to Deposit Account No. 02-24	<u>48</u> .				uivo (27 CED	
1 1	OTE: Where a .137(a) or (b)) m	n appropriate time limit und oust be filed and granted to re	er 37 CFR 1.494 or 1.495 estore the application to p	nas not been ending statu /////	met, s.	, a petition to re	vive (3/ CFR	
В	nd all correspondence irch, Stewart, K.O. Box 747	e to: olasch & Birch, LLP		SIGNA	TURE	Jubble #3	Sort	_
F	alls Church, VA 703)205-8000	22040-0747	U	SVEN)N, LEONARD I	<u>R.</u>	
				#30,3		ION NUMBER		

/LRS/sas October 8, 1999

His office of the control of the con

PATENT 365-428PCT

IN THE U.S. PATENT AND TRADEMARK OFFICE

Applicant: KOISTINEN, Jari et al

Int'l. Appl. No.: PCT/FI98/00329

Appl. No.: New Group: Unknown

Filed: October 8, 1999 Examiner: UNKNOWN

For: POLYOL AND COMPLEX ESTERS FOR USE

WITH, IN PARTICULAR, FLUORINATED

REFERIGERANTS

PRELIMINARY AMENDMENT

BOX PATENT APPLICATION

Assistant Commissioner for Patents Washington, DC 20231

October 8, 1999

Sir:

The following Preliminary Amendments and Remarks are respectfully submitted in connection with the above-identified application.

AMENDMENTS

IN THE SPECIFICATION:

Please amend the specification as follows:

Before line 1, insert --This application is the national phase under 35 U.S.C. § 371 of PCT International Application No. PCT/FI98/00329 which has an International filing date of April 14, 1998, which designated the United States of America.--

REMARKS

The specification has been amended to provide a crossreference to the previously filed International Application.

If necessary, the Commissioner is hereby authorized in this, concurrent, and future replies, to charge payment or credit any overpayment to Deposit Account No. 02-2448 for any additional fees required under 37 C.F.R. § 1.16 or under 37 C.F.R. § 1.17; particularly, extension of time fees.

Respectfully submitted,

BIRCH, STEWART, KOLASCH & BIRCH, LLP

Svensson,

LRS/sas 365-428PCT Box 747

Alls Church, VA 703) 205-8000 22040-0747

(Rev. 03/30/99)

PCT/FI98/00329

514 Rec'd **PCT/PTO** 0 8 OCT 1999

1

Polyol and complex esters for use with, in particular, fluorinated refrigerants

The present invention concerns a refrigerant compositions according to the preambles of claims 1, 3, 5 and 7. Compositions of this kind generally contain a non-chlorinated hydrofluorocarbon based refrigerant composition together with a polyol ester based lubricant mixed therewith.

The invention also concerns complex esters according to claim 16 and the use thereof in lubricants.

10

5

Lately, as a result of development in many fields of application, the evolution of polyolester type lubricants has been rapid. These products can be used as such or mixed with another base oil, such as a hydrocarbon, in engine oils for automotives, in aeroplane and gas turbine oils, as biodegradable hydraulic oils, as metal working oils and as compressor oils. These products are used in particular together with fluorinated refrigerants as a soluble lubricant component in refrigeration compressors due to their advantageous solubility properties, good technical stability and good cold properties.

20

15

The use of, e.g., neopentylglycol and pentaerytritol esters together with refrigerants has been generally suggested. Although these known esters in principle exhibit good lubricant properties, their solubility in non-chlorinated hydrofluorocarbons is often only fair. For this reason they do not work well enough in refrigerant compositions containing fluorinated hydrocarbons.

25

It is an object of the present invention to eliminate the problems of the prior art and to provide polyol and complex esters of a novel kind which can be used in particular together with fluorinated refrigerant liquids as lubricants. It is another object of the invention to provide novel esters which are generally suited to the use as base oils of lubricants.

30

35

The present invention is based on the finding that polyol or complex esters of 3-hydroxy-2,2-methyl-3-hydroxy-2,2-dimethylpropionate, i.e. hydroxypivalyl hydroxypivalate, which have good lubricant properties, also exhibit a good or excellent solubility in fluorinated refrigerants and they are therefore suitable for use in refrigerant compositions containing this kind of refrigerants. In particular the polyol esters used comprise the polyol HPHP (hydroxypivalyl hydroxypivalate) as such or together with another polyol, such as NPG, BEPD, ETHD, TMP, TME or PE and the carboxylic acid is a linear or branched C₅ - C₁₈

monocarboxylic acid or a hydroxy acid, such as hydroxypivalic acid or a mixture of monoand dicarboxylic acids, such as adipic acid, sebasic acid, azelaic acid, dimethylmalonic acid or cyclic anhydrides.

More specifically, the refrigerant composition according to the present invention is mainly characterized by what is stated in the characterizing parts of claims 1, 3, 5 and 7.

Complex esters of HPHP are novel and useful as base oils of lubricant oils. The novel esters are characterized by what is stated in the characterizing part of claim 16.

10

15

The present invention provides considerable advantages. Thus, as mentioned above, the esters of HPHP have good lubricant properties and good solubility in HFC compounds used as refrigerants. The raw materials of said oils can be produced by the economically advantageous oxo-process (hydroformulation). The properties of the oils can easily be modified depending on the application by varying the ratio of the polyols of the ester (the amount of HPHP can be 100 to 5 mol-% of the total amount of polyol), the esterifying carboxylic acid and/or the ratio between the esterifying carboxylic acids. By using branched acids the solubility can be improved and by using dibasic acids the viscosity can be raised.

20

In the following, the invention will be examined with the aid of a detailed description and using a number of working examples.

The present esters comprise polyol or complex esters of 3-hydroxy-2,2-methyl-3-hydroxy-2,2-dimethylpropionate. "Polyol ester" means i.a. esters having a carboxylic group comprising a monobasic acid or an anhydride thereof. For the purpose of the present invention, the term "polyol ester" comprises generally also "complex esters" which are esters in which at least a part of the esterifying acids are dibasic. Usually both carboxylic groups of these acids react with an alcohol and yield oligomeric ester compounds, which contain at least two alkohol residues and one carboxylic acid residue. Complex esters also include esters having the carboxylic acid residue formed by a hydroxy acid containing both a hydroxyl group and a carboxylic group. The carboxylic group reacts with the polyol, whereas the hydroxyl group reacts with the carboxylic group of another carboxylic acid.

"Polyol" stands for a compound with at least two hydroxy groups. According to the present invention HPHP can be esterified alone or together with another polyol. These polyols are,

e.g., NPG (neopentylglycol), BEPD (2-butyl-2-ethyl-1,3-propanediol), ETHD (2-ethyl-1,3-hexanediol), TMP (trimethylol propane), TME (trimethylol ethane), PE (pentaerythritol), TMPD (2,2,4-trimethyl-pentanediol) and CHDM (1,4-dimetylol-cyclohexane). Of these polyols chemically and technically stable polyols, containing no hydrogen in the carbon in position 2 or which are (sterically) strongly hindered, such as NPG, ETHD, CHDM and BEPD, are particularly preferred.

Preferably the polyol ester mixtures are formed by mixing the polyols together and by esterifying the thus formed mixture *in situ*.

10

5

According to a first preferred embodiment of the invention, a refrigerant composition is provided, comprising a polyol ester which completely or almost completely (95 mol-%, or even 100 %) consists of an ester of HPHP.

15

According to a second preferred embodiment of the present invention, a refrigerant composition is provided, comprising in addition to a polyol ester of HPHP an ester of TMP, TME, PE or TMPD at any ratio. Preferably HPHP forms the main part of the polyol residue of the ester mixture, i.e. its molar amount is 50 % - 100 %.

20

According to a third preferred embodiment of the present invention, a refrigerant composition is provided, comprising in addition to a polyol ester of HPHP a polyol ester of BEPD, the molar ratio between BEPD and HPHP being 5:95 to 99:1.

25

According to a fourth preferred embodiment of the present invention, a refrigerant composition is provided, comprising in addition to a polyol ester of HPHP a polyol ester of NPG, ETHD or CHDM.

30

HPHP or a mixture of HPHP and some other polyol is esterified with a linear or branched C_4 to C_{18} carboxylic acid or an anhydride thereof. As specific examples of aliphatic, linear or branched, saturated or unsaturated C_4 - C_{18} -carboxylic acids which can be used for preparing the ester, the following can be mentioned:

v

I saturated, linear C₄-C₁₈-carboxylic acids: butanoic acid (butyric acid), pentanoic acid (valeric acid), hexanoic acid (caproic acid), heptanoic acid, octanoic acid (caprylic acid), decanoic acid (capric acid), dodecanoic acid (lauric acid) and hexadecanoic acid (palmitic acid) and mixtures thereof;

- II saturated, branched C₄-C₁₆-carboxylic acids: isobutanoic acid, 2-ethylhexanoic acid, isononanoic acid and 3,5,5-trimethylhexanoic acid;
- III unsaturated, linear C₄-C₁₈-carboxylic acids: 3-butenoic acid (vinylacetic acid); and
- IV unsaturated, branched C₄-C₁₈-carboxylic acids.

In the mixed esters the ratios between the various linear and branched carboxylic acids can vary within large boundaries. Typically, the linear carboxylic acid(s) is (are) present in amounts of 1 to 100 mol-%, preferably about 10 to 90 mol-% of the amount of carboxylic acids. Correspondingly, the amount of branched carboxylic acids is 99 to 1 mol-%, preferably about 90 to 10 mol-%. In particular it is possible to prepare polyolesters, which contain 10 to 50 mol-% of at least one linear carboxylic acid and 90 to 50 mol-% of a branched carboxylic acid.

10

15

When polyol esters of HPHP are prepared it is preferred to select linear or branched acids containing 4 to 14 carbon atoms as esterifying carboxylic acid. Octanoic acid, 2-ethylhexanoic acid and lauric acid can be mentioned as examples.

20

Esterifying hydroxy acids are, e.g., hydroxypivalic acid (HPAA), lactic acid, citric acid and dimethylolpropionic acid (DMPA).

In addition to the afore-mentioned, the esterifying carboxylic acid used can comprise dibasic carboxylic acids, such as oxalic acid, malonic acid, dimethylmalonic acid, succinic acid, glutaric acid, adipic acid, sebacic acid, pimelic acid, suberic acid and azelaic acid. It is also possible to use cyclic anhydrides, such as succinic anhydride or alkyl derivaties thereof, or trimellitic anhydride. Small amounts of aromatic anhydrides, such as phthalic anhydride are also possible.

25

The degree of esterification of the polyols is 50 to 100 %, preferably as high as possible, at least about 90 %. In the complex esters the ratio between the mono- and dibasic carboxylic acids is 50:50 to 99:1.

30

35

The polyol esters/mixed esters/complex esters of HPHP or HPHP and at least another polyol can be used for preparing refrigerant compositions. These contain as a refrigerant one or several chlorine-free hydrofluorocarbon(s) (a refrigerant) in which the ester is dissolved. As specific examples of the refrigerant liquid component of the compositions, the following can be mentioned: hydrofluorocarbon 134 (1,1,2,2-tetrafluoroethane),

10

15

20

hydrofluorocarbon 134a, hydrofluorocarbon 143 (1,1,2-trifluoroethane), hydrofluorocarbon 143a (1,1,1-trifluoroethane), hydrofluorocarbon 152 (1,2-difluoroethane) and hydrofluorocarbon 152a (1,1-difluoroethane). Of these compounds, hydrofluorocarbon 134a is generally preferred. Mixtures of hydrofluorocarbons can also be employed. Examples include hydrofluorocarbon mixture 407 (mixture of hydrocarbons 32, 125 and 134a) and hydrofluorocarbon mixture 410 (mixture of hydrocarbon 32 and 125).

Depending on application, the viscosity requirement for the ester is, according to ISO-standard, between 5 and 200 cSt (40 °C). Low (5 - 10) and intermediate (22 - 32) viscosities are needed for, e.g., refrigerators and other small refrigeration devices. High viscosity (46 - 68) compositions are used for, e.g., cooling equipment of air conditioners.

As already mentioned in the beginning, the viscosity of the prepared esters can be adjusted as desired by suitably selecting esterifying carboxylic acid components and/or by adding a further polyol to the BEPD. Thus, by using conventional linear or branched carboxylic acids (C_4 - C_{12}) and, e.g., adipic acid, it is possible to prepare esters having viscosities in the range of about 15-22 cSt at 40 °C. Their viscosity indeces are about 100 and pour points below -40 °C. They are suitable for use in smallish cooling equipment. By increasing the amount of a branched carboxylic acid it is possible to increase the solubility of the esters. By feeding a dibasic carboxylic acid into the esterification reaction and in particular by using it together with linear or branched acids, the viscosity of the product can be increased. The cold properties and good solubility remain. Mixing HPHP with another polyol before esterification makes it possible to increase even further without impairing the solubility . The viscosity increase to the range of high viscosity.

25

30

As examples of particularly valuable esters, the following can be mentioned:

- I Polyol esters of HPHP, which contain 30 to 60 % linear-carboxylic acid and 70 to 40 mol-% branched carboxylic acid
- II Complex esters of HPHP which contain 1 to 10 mol-% dibasic carboxylic acid and 90 to 99 mol-% linear and/or branched monobasic carboxylic acid; and
- III Complex esters of HPHP and NPG/BEPD, which contain 4 to 30 mol-% dibasic carboxylic acid and 96 to 70 mol-% linear and/or branched monobasic carboxylic acid.

35

As mentioned above, the complex esters of HPHP as well as complex esters of HPHP and

10

15

20

25

30

35

some other polyol, are already as such novel products which can be used in lubricant compositions for different aims. The esters work as base oil of these compositions and additives are usually employed in amounts of 0 to 20 wt.-% in the compositions for the purpose of modifying the compositions such that they are better suited for various applications. Thus, the esters are suitable not only for use in refrigerant compositions but also for all applications mentioned in the introduction of the specification.

Conventional additives which can be used in the refrigerant liquid compositions include, e.g., the following: antioxidants, antiwear agents, detergents, defoaming agents and corrosion inhibitors.

Suitable antioxidants include phenols, such as 2,6-di-t-butyl-4-methylphenol and 4,4'-methylene-bis(2,6-di-t-butylphenol); aromatic amines, such as p,p-dioctylphenylamine, monooctyldiphenylamine, phenothiazine, 3,7-dioctylphenothiazine, phenyl-1-naphthylamine, phenyl-2-naphthylamine, alkylphenyl-1-naphthatalamines and alkylphenyl-2-naphthal-amines, as well as sulphur-containing compounds, e.g. dithiophosphates, phosphitest, sulphides and dithio metal salts, such as benzothiazole, tin-dialkyldithiophosphates and zinc diaryldithiophosphates.

Suitable antiwear agents include, for example, phosphates, phosphate esters, phosphites, thiophosphites, e.g. zinc dialkyl dithiophosphates, zinc diaryldithiophosphates, tricresyl phosphates, chlorinated waxes, sulphurised fats and olefins, such as thiodipropionic esters, dialkyl sulphides, dialkyl polysulphides, alkyl-mercaptanes, dibenzothiophenes and 2,2'-dithiobis(benzothiazole); organic lead compounds, fatty acids, molybdenum complexes, such as molybdenum disulphide, halogen substituted organosilicon compounds, organic silicon compounds, borates and halogen-substituted phosphorus compounds.

As specific examples of suitable detergents, the following should be mentioned: sulphonates, aromatic sulphonic acids, which are substituted with alkyl having a long chain, phosphonates, thiophosphonates, phonolates, metal salts of alkylphenols, and alkyl sulphides.

Typical defoaming agents include silicon oils, e.g. dimethylpolysilozane and organic silicon compounds such as diethyl silicates.

Organic acids, amines, phosphates, alcohols, sulphonates and phosphites are examples of

10

15

20

25

corrosion inhibitors.

The esters according to the invention are prepared by a conventional esterification reaction wherein a polyol or a mixture of polyols is (are) reacted with an acid mixture in the presence of a catalyst or without a catalyst. Various acids, such as sulphuric acid, hydrochloric acid, p-toluene sulphonic acid, butyl titanate, tinoxide etc., are suitable catalysts for carrying out the invention. A particularly advantageous catalyst is tinoxide.

During the reaction, the polyol is reacted with the acid component by using an equivalent amount of acid, a deficient amount of acid or a surplus of acid; the excess acid amounts to typically a maximum of 10 mol-%, preferably about 0.1 to 5 mol-%, in particular about 1 mol-%. The reaction temperature is 150 to 230 °C, preferably 170 to 220 °C and in particular about 190 to 210 °C.

The esterification can be carried out as a batch or semibatch process for example by adding the remaining acid later on. The most typical embodiment comprises carrying out esterification in the melt phase but it is also possible to use a hydrocarbon-type medium, such as toluene or xylene. The product is neutralized either with conventional bases (NaOH, NaHCO₃, Na₂CO₃ etc.) or with organic amines and are then washed. The degree of purification of the ester product is preferably over 85 %, in particular over 90 % and the acid number of the ester is preferably below 0.1 mg KOH/g.

The following examples illustrate the invention. They do not, however, limit the scope of the invention.

Example 1

Determination of ester solubility

Solubility in fluorinated hydrocarbons was determined as follows: 1 ml of the studied ester was put into a test tube which was closed with a stopper. The test tube was placed in a cold bath at a temperature of -30 °C. When the temperature of the test tube and the ester had reached -30 °C (after about 5 minutes), a fluorinated refrigerant, such as R-134a, was added to make a total volume of 10 ml.

35 The ester-refrigerant mixture was allowed to stand in the bath at -30 °C with possibly a light occasional stirring. After about 15 minutes the mixture was visually assessed and it

was determined whether the mixture contained one or two phases. If the ester and the refrigerant liquid formed one phase, the ester is completely dissolved in the refrigerant liquid. If there are two phases present in the mixture, the ester is either partially or completely insoluble in the refrigerant liquid.

5

Example 2

Preparation of esters of HPHP

The preparation of esters of HPHP is described in the following using the esters of HPHP and heptanoic acid as an example.

The raw materials were weighed into a glass bulb according to the following recipe: HPHP 50 g and heptanoic acid 64.6 g. The catalyst used comprised 0.17 g tinoxide. The esterification was carried out by stirring using a mixer with an electric motor and by nitrigating the reaction mixture at about 210 °C. The reaction was complete wihin 7 hours.

Tinoxide was removed by filtration. Excess acid was neutralized from the reaction mixture with 2 - 5 wt-% triethylamine. The neutralization was carried out at 80 °C for 3 hours. Warm water (2 - 5 wt-%) was added to the reaction mixture and it was mixed cautiously. The solvent of the reaction mixture comprised heptane. Any formed aminocarboxylic acid salt or complex was separated. The solvent and the unreacted triethylamine were removed by vacuum distillation. The end product was filtered. The results are summarized in Table 1.

25

Table 1. Polyol esters of HPHP

Sample	Polyol	Acids (mol-%)	V ₄₀	V ₁₀₀	VI	PP(°C)	Solubility in R-134a	
							-30 °C	-50 °C
1	НРНР	Heptanoic acid (100)	11.63	2.98	111	-	Excellent	Excellent

10

15

20

Example 3

Preparation of esters of HPHP from acyclic anhydrides

The preparation of esters of HPHP is illustrated by using the preparation of an ester of HPHP and isobutyric anhydride as an example.

The raw materials were weighed into a glass reactor according to the following recipe: HPHP 17.5 g and isobutyric anhydride 19.36 g. The catalyst used comprised 0.37 g methanesulphonic acid. The esterification was carried out by adding the anhydride and the catalyst from a dropping funnel to the HPHP during 2 hours, and then the reaction mixture was stirred at about 150 °C for 2 hours.

Excess acid was neutralized from the reaction mixture and the catalyst was washed in a separation funnel with 3×25 ml 5% sodium carbonate solution and 3×25 ml water. Any sodium salt or complex of the carboxylic acid were separated. Finally, the product was dried on sodium sulphate and filtered. Other esters were prepared by suitable modification of the conditions. The results are summarized in Table 2.

Table 2. Acid anhydride esters of HPHP

Sample	Polyol	Acids (mol-%)	V_{40}	\mathbf{V}_{100}	VI	Solubility in R-134a	
						-30 °C	-50 °C
2	HPHP	Isobutyric anhydride	7.44	2.14	82	Excellent	
3	HPHP	2-ethylbutanoic anhydride	11.84	2.79	64	Excellent	Excellent

25

Example 4

Preparation of complex esters of HPHP

30

35

Cmplex esters of HPHP is described using the ester of HPHP, octanoic acid and adipic ester as an example.

The raw materials were weighed into a glass reactor according to the following recipe: HPHP 100 g, octanoic acid 94.8 g and adipic acid 24.0 g. The catalyst used comprised

10

15

20

25

0.328 g tinoxide. acid. The esterification was carried out by stirring and nitrigating the reaction mixture at about 210 °C. The reaction was complete within 7 hours.

Excess acid was neutralized from the reaction mixture with 5 wt-% triethylamine. The neutralization was carried out at 80 °C for 3 hours. Warm water (5 wt-%) was added to the reaction mixture and it was mixed cautiously. Any formed aminocarboxylic acid salt or complex was separated. The reaction mixture was then washed with a dilute mineral acid (1 molar H₃PO₄) and subsequently 1 to 2 times with warm water. Finally, the product was dried on sodium sulphate and filtered. Other esters were prepared by suitable modification of the conditions. The results are summarized in Table 3.

Table 3. Complex esters of HPHP

Sample	Polyol	Acids (mol-%)	V ₄₀	V ₁₀₀	VI	PP(°C)	Solubii R-13	
		(4.222 1.7)					-30 °C	−50 °C
4	НРНР	C ₈ (80) AA (20)	39.8	7.06	140	-51	Good	
5	HPHP	C ₈ (80) SA (20)	50.5	8.75	154	-51	Excellent	Excellent
$A_A = adig$	oic acid	SA = s	ebasic a	cid	C ₈	= octanoio	e acid	

Example 5

Preparation of polyol/complex esters of HPHP

Following the process of Example 4 complex esters of mixtures of HPHP and some other polyols were prepared. The results are indicated in Table 4.

Table 4. Polyol/complex esters of HPHP

5	Sample	Polyol	Acids (mol-%)	V ₄₀	V ₁₀₀	VI	PP(°C)	Solubility in R-134a	
			` ,					−30 °C	-50 °C
	6	HPHP (60) BEPD (40)	C ₈ (90) AA (10)	19.78	4.32	128	-63	Fair	
	7	HPHP (60) BEPD (40)	C ₈ (80) AA (20)	33.20	6.15	136	-54	Good	
	8	HPHP (90) BEPD (10)	C ₈ (90) AA (10)	21.57	4.61	133	-60	Excellent	Excellent
	9	HPHP (60) NPG (40)	C ₈ (80) AA (20)	23.69	5.06	147	-63	Excellent	
10	10	HPHP (90) BEPD (10)	C ₈ (80) AA (20)	32.83	6.14	137	-60	Excellent	

 $BEPD = 2\text{-butyl-}2\text{-ethyl-}1, \\ 3\text{-propanediol}, NPG = neopentylglycol$

Helicle 34 June hund

1 5 -06- 1999

Claims:

5

10

15

- 1. Refrigerant composition comprising a chlorine-free hydrofluorocarbon based refrigerant and, mixed therewith, a lubricant containing a polyol ester, c h a r a c t e r i z e d in that the polyol ester comprises a mixture of an ester of 3-hydroxy-2,2-dimethyl-propyl-3-hydroxy-2,2-dimethyl-propionate and
 - an ester of trimethylol propane, trimethylol ethane, pentaerythritol or 2,2,4 trimethylpentadiol, the amount of the 3-hydroxy-2,2-dimethyl-propyl-3-hydroxy 2,2-dimethylpropionate being at least 50 mol-% of the polyol residue of the ester mixture,
 - an ester of 2-butyl-2-ethyl-1,3-propanediol, the molar ratio of the 2-butyl-2-ethyl-1,3-propanediol and the 3-hydroxy-2,2-dimethyl-propyl-3-hydroxy-2,2-dimethylpropionate being 5:95 99:1, or
 - a polyol ester of neopentylglycol, 2-ethyl-1,3-hexanediol or 1,4-dimethylol-cyclohexane.
 - 2. The refrigerant composition according to claim 1, wherein the polyol ester mixture is prepared *in situ*.
- 3. The refrigerant composition according to clam 1 or claim2, wherein the carboxylic acid residue of the polyol ester is derived from a linear or branched C₄...C₁₈-carboxylic acid, or an anhydrides thereof, or it is derived from a mixture of linear or branched C₄...C₁₈-carboxylic acids or anhydrides thereof.
- 4. The refrigerant composition according to claim 3, wherein the carboxylic acid residue is derived from 2-ethylhexanoic acid, heptanoic acid, octanoic acid and/or lauric acid.
 - 5. The refrigerant composition according to claim 1, wherein the carboxylic acid residue of the ester is derived from a mixture of mono- and dibasic carboxylic acids.
 - 6. The refrigerant composition according to claim 5, wherein the monobasic carboxylic acid residue is derived from linear or branched C₄...C₁₈-carboxylic acids or anhydrides or mixtures thereof.
- 7. The refrigerant composition according to claim 5 or claim 6, wherein the dibasic carboxylic acid residue is derived from oxalic acid, malonic acid, dimethylmalonic acid,

Article 34 Annedment-

succinic acid, glutaric acid, adipic acid, sebasic acid, pimelic acid, suberic acid or azelaic acid, or a cyclic anhydride such as succinic anhydride or an alkyl derivative thereof, or trimellitic anhydride.

- 8. The refrigerant composition according to any of claims 5 to 7, wherein the molar ratio between the mono- and dibasic carboxylic acids is 50:50 to 95:5.
 - 9. The refrigerant composition according to any of the preceding claims, wherein the fluorinated hydrocarbon based refrigerant is hydrofluorocarbon 134, hydrofluorocarbon 134a, hydrofluorocarbon 143a, hydrofluorocarbon 152 or hydrofluorocarbon 152a or a mixture of hydrofluorocarbons.
 - 10. Complex esters of 3-hydroxy-2,2-dimethyl-propyl-3-hydroxy-2,2-dimethylpropionate which contain residues of both mono- and dibasic carboxylic acids, the molar ratio between the mono- and dibasic carboxylic acid residues in the ester being 50:50 to 95:5.
 - 11. The complex esters according to claim 10, wherein the monobasic carboxylic acid residues are derived from linear or branched $C_4...C_{18}$ -carboxylic acids or anhydrides or mixtures thereof.
 - 12. The complex esters according to claim 10 or claim 11, wherein the dibasic carboxylic acid residues are derived from oxalic acid, malonic acid, dimethyl malonic acid, succinic acid, glutaric acid, adipic acid, sebasic acid, pimelic acid, suberic acid or azelaic acid, or a cyclic anhydride such as succinic anhydride or an alkyl derivative thereof, or trimellitic anhydride.
 - 13. The complex esters according to any of claims 16 to 19, mixed with esters and/or complex esters of another polyol.
- 30 14. The complex esters according to claim 13, wherein the esters are in a mixture of esters and/or complex esters of NPG or BEPD.
 - 15. The use of an ester according to any of claims 10 to 14 as base oils for lubricants.

 10

15

20

BIRCH, STEWART, KOLASCH & BIRCH, LLP

PLEASE NOTE: YOU MUST

COMBINED DECLARATION AND POWER OF ATTORNEY

ATTORNEY DOCKET NO. 365-428P

FOR PATENT AND DESIGN APPLICATIONS

FOLLOWING:	As a below named inven					
#	stated next to my name; that is named below) or an original					
	matter which is claimed and				stow) or ure	e subjec
Insert Title:	Polyol and compl	ex esters for	use with, in par	cticular,		
	fluorinated refr					
Fill in Appropriate	d			^ 		
Information -	the specification of which is					
For Use Without					_ as	
Specification Attached:		•			/ Or	
	the specification	on was filed on	April 14, 1998	3 &	_ as PCT	
	International App	olication Number	PCT/FI98/00329	ير <u>9</u>	d was	
	amended under I	PCT Article 19 on		(if applic	able)	
	I hereby state that I ha	ive reviewed and ting	lerstand the contents	of the above ider	tified spec	ification
	including the claims, as ame					
	I acknowledge the duty	to disclose informat	ion which is material	to patentability as	defined in	Title 37
	Code of Federal Regulation	s, §1.56.				
	I do not know and do n					
76 G ts	my or our invention thereof					
-44	our invention thereof or mo	ore than one year pri	or to this application,	that the same was	not in publ	ic use o
44	on sale in the United States of been patented or made the					
rijas Mas	country foreign to the Unit					
#1 4 #4 8	assigns more than twelve mo					
4.9	patent or inventor's certific					
	America prior to this applic	ation by me or my le	gal representatives or	assigns, except as f	follows.	
**;	I hereby claim foreign					
ļu:	application(s) for patent o					
•	application for patent or in	iventor's certificate h	aving a filing date be	tore that of the ap	oplication of	on which
Insert Priority	priority is claimed:					
Information:	Prior Foreign Application 971548	on(s)		4 4007 4	Priority	Claimed
ः(if appropriate)				1, 1997 -	X	
4.8 4.8	(Number) 971549 /	(Country) Finland	(Month/Day April 1	/Year Filed) 1, 1997 ~	Yes	No
4. ⁴ 43	(Number)	(Country)	(Month/Day		X Var	□ Na
4.35	980730 -	Finland		1, 1998 V	Yes ☒	No
	(Number)	(Country)	(Month/Day		Yes	No.
	(Number)	(Country)	(Month/Day	/Year Filed)	Yes	No
	(Number)	(Country)	(Month/Day	/Vear Filed)	☐ ¥Z	
	I hereby claim the ben	·			Yes ed States pro	No ovisiona
Insert Provisional	application(s) listed below.	ciii ailaci Tiac 55, c	inted states code, gr	15(c) of any office	d blates pr	OVISIOIIA
Application(s):						
(if any)	(Application Number)			(Filing Date)		
	(Application Number)			(Filing Date)	· 1016	
	All Foreign Applications, i				Than 12 M	onths (
Insert Requested	Months for Designs) Prior	To The Filing Date	of This Application: Application No.		Filing (Month	h /Dou/Vens
Information:	Country		Application No.		rang (Mont	1/ Day/ Ical
(if appropriate)						
	I hereby claim the ben-	efit under Title 35. U	Inited States Code, \$1	20 of any United S	States appli	cation(s
	listed below and, insofar as			•		
	prior United States applicat					
	§112, I acknowledge the du	ty to disclose informa	tion which is material	l to patentability as	defined in	Title 37
	Code of Federal Regulation					
T 4 D 1 710	and the national or PCT in	ernational filing date	e of this application:			
Insert Prior U.S. Application(s):	>					
(if any)	(Application Number)	(Fil	ing Date)	(Status - patented, pen	ding, abandoned)	

(Filing Date)

(Status - patented, pending, abandoned)

(Application Number)

I hereby appoint the following attorneys to prosecute this application and/or an international application based on this application and to transact all business in the Patent and Trademark Office connected therewith and in connection with the resulting patent based on instructions received from the entity who first sent the application papers to the attorneys identified below, unless the inventor(s) or assignee provides said attorneys with a written notice to the contrary:

(Reg. No. 21,066) Terrell C. Birch Raymond C. Stewart (Reg. No. 19,382) (Reg. No. 22,463) James M. Slattery (Reg. No. 28,380) Joseph A. Kolasch Bernard L. Sweeney (Reg. No. 24,448) Michael K. Mutter (Reg. No. 29,680) Gerald M. Murphy, Jr. (Reg. No. 28,977) (Reg. No. 29,271) Charles Gorenstein (Reg. No. 30,330) Terry L. Clark (Reg. No. 32,644) Leonard R. Svensson (Reg. No. 32,868) (Reg. No. 32,181) Andrew D. Meikle Marc S. Weiner (Reg. No. 32,334) Donald J. Daley (Reg. No. 34,313) Joe McKinney Muncy (Reg. No. 32,350) C. Joseph Faraci

Send Correspondence to:

BIRCH, STEWART, KOLASCH & BIRCH, LLP

P.O. Box 747 • Falls Church, Virginia 22040-0747 Telephone: (703) 205-8000 • Facsimile: (703) 205-8050

PLEASE NOTE: YOU MUST COMPLETE THE FOLLOWING:

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

-1-3 									
Full Name of First or Sole Inventor:	GIVEN NAME	FAMILY NAME	INVENTOR'S SIGNATURE	•	DATE*				
Insert Name of Inventor Insert Date This	<u>Jari</u>	Koistinen	1000		September 20, 1999				
Document is Signed UU	Residence (City, Stat	te & Country)		CITIZENSHIP					
Insert Residence Insert Citizenship	Jyväskylä,	Finland FiX	Finnish ~						
44 44	POST OFFICE ADDRESS (Complete Street Address including City, State & Country)								
Insert Post Office Address	Lamminmutka	a 2 C 14, FIN-4052	0 Jyväskylä, Finland						
ंः ः Full Name of Second	GIVEN NAME	FAMILY NAME	INVENTOR'S SIGNATURE		DATE*				
Inventor, if any:	Kari	Rissanen	1 K		September 20, 1999				
See above	Residence (City, State	te & Country)		CITIZENSHIP	<u> </u>				
	<u>Hankasalmi</u>	, Finland FIX	Finnish	l .					
1200	POST OFFICE ADDR	RESS (Complete Street Address	including City, State & Country)	<u> </u>	- 0				
	Hankamäent:	ie 13, FIN-41520 H	ankasalmi, Finland						
Full Name of Third	GIYEN NAME	FAMILY NAME	INVENTOR'S SIGNATURE	1	DATE*				
Inventor, if any	<u>Laura</u>	Silvennoinen	Xaura filve	MAGINEN	September 20, 1999				
See above	Residence (City, Star		•	CITIZENSHIP					
	J <u>yväskylä</u> ,	Finland FIX		Finnish	1				
	POST OFFICE ADDR	RESS (Complete Street Address	including City, State & Country)						
	Kilpisenka	tu 16 A 20, FIN-40	100 Jyväskylä, Finla	nd					
Full Name of Fourth Inventor, if any	GIVEN NAME	FAMILY NAME	INVENTOR'S SIGNATURE	/ _	DATE* September 20,				
	Salme	Koskimies,	yall for	<i>>-7</i>	1999				
set and	Residence (City, State & Country)			CITIZENSHIP					
	Helsinki, Finland FiX			Finnish					
	POST OFFICE ADDRESS (Complete Street Address including City, State & Country)								
	Hämeenapaj	antie 7, FIN-00850	Helsinki, Finland						
Full Name of Fifth Inventor, if any	GIVEN NAME FAMILY NAME		INVENTOR'S SIGNATURE		DATE*				
see above			<u></u>						
	Residence (City, Sta	te & Country)		CITIZENSHIP					
			·	<u> </u>					
	POST OFFICE ADDF	RESS (Complete Street Address	including City, State & Country)						
		-							
Page 2 of 2	* DATE OF SIGNATUR	RE							

(USPTO Approved 3-90) (Revised 8-97)